

# **CS 241: Systems Programming**

## **Lecture 13. Bits and Bytes 2**

Fall 2019

Prof. Stephen Checkoway

# Internal data representation

Data are stored in binary

32 bit unsigned integer values are:

# Internal data representation

Data are stored in binary

32 bit unsigned integer values are:

00000000 00000000 00000000 00000000 = 0

# Internal data representation

Data are stored in binary

32 bit unsigned integer values are:

00000000 00000000 00000000 00000000 = 0

00000000 00000000 00000000 00000001 = 1

# Internal data representation

Data are stored in binary

32 bit unsigned integer values are:

00000000 00000000 00000000 00000000 = 0

00000000 00000000 00000000 00000001 = 1

00000000 00000000 00000000 00000010 = 2

# Internal data representation

Data are stored in binary

32 bit unsigned integer values are:

00000000 00000000 00000000 00000000 = 0

00000000 00000000 00000000 00000001 = 1

00000000 00000000 00000000 00000010 = 2

00000000 00000000 00000000 00000011 = 3

# Internal data representation

Data are stored in binary

32 bit unsigned integer values are:

00000000 00000000 00000000 00000000 = 0

00000000 00000000 00000000 00000001 = 1

00000000 00000000 00000000 00000010 = 2

00000000 00000000 00000000 00000011 = 3

...

11111111 11111111 11111111 11111111 =  $2^{32}-1$

# Bitwise operators

Binary operators apply the operation to the corresponding bits of the operands

- ▶  $x \ \& \ y$  — bitwise AND
- ▶  $x \ | \ y$  — bitwise OR
- ▶  $x \ ^ \ y$  — bitwise XOR

Unary operator applies the operation to each bit

- ▶  $\sim x$  — one's complement (flip each bit)



# Review of Boolean logic

| A | B | $\sim A$ | A&B | A   B | A ^ B |
|---|---|----------|-----|-------|-------|
| 0 | 0 | 1        | 0   | 0     | 0     |
| 0 | 1 | 1        | 0   | 1     | 1     |
| 1 | 0 | 0        | 0   | 1     | 1     |
| 1 | 1 | 0        | 1   | 1     | 0     |

What is the value of  $0x4E$  &  $0x1F$ ?

- A.  $0xE$
- B.  $0x51$
- C.  $0x5F$
- D.  $0xB1$
- E.  $0xE0$

| Hex Binary |      | Hex Binary |      |
|------------|------|------------|------|
| 0          | 0000 | 8          | 1000 |
| 1          | 0001 | 9          | 1001 |
| 2          | 0010 | A          | 1010 |
| 3          | 0011 | B          | 1011 |
| 4          | 0100 | C          | 1100 |
| 5          | 0101 | D          | 1101 |
| 6          | 0110 | E          | 1110 |
| 7          | 0111 | F          | 1111 |

# Bit shifting

# Bit shifting

Manipulates the position of bits

# Bit shifting

Manipulates the position of bits

- ▶ Left shift fills with 0 bits

# Bit shifting

Manipulates the position of bits

- ▶ Left shift fills with 0 bits
- ▶ Right shift of **unsigned** variable fills with 0 bits

# Bit shifting

Manipulates the position of bits

- ▶ Left shift fills with 0 bits
- ▶ Right shift of **unsigned** variable fills with 0 bits
- ▶ Right shift of **signed** variable fills with sign bit (Actually implementation defined if negative!)

# Bit shifting

Manipulates the position of bits

- ▶ Left shift fills with 0 bits
- ▶ Right shift of **unsigned** variable fills with 0 bits
- ▶ Right shift of **signed** variable fills with sign bit (Actually implementation defined if negative!)

`x << 2; //` shifts bits of `x` two positions left



# Bit shifting

Manipulates the position of bits

- ▶ Left shift fills with 0 bits
- ▶ Right shift of **unsigned** variable fills with 0 bits
- ▶ Right shift of **signed** variable fills with sign bit (Actually implementation defined if negative!)

`x << 2; //` shifts bits of `x` two positions left

- ▶ Same as multiplying by 4

# Bit shifting

Manipulates the position of bits

- ▶ Left shift fills with 0 bits
- ▶ Right shift of **unsigned** variable fills with 0 bits
- ▶ Right shift of **signed** variable fills with sign bit (Actually implementation defined if negative!)

`x << 2; //` shifts bits of `x` two positions left

- ▶ Same as multiplying by 4

`x >> 3; //` shifts bits of `x` three positions right

# Bit shifting

Manipulates the position of bits

- ▶ Left shift fills with 0 bits
- ▶ Right shift of **unsigned** variable fills with 0 bits
- ▶ Right shift of **signed** variable fills with sign bit (Actually implementation defined if negative!)

`x << 2; //` shifts bits of `x` two positions left

- ▶ Same as multiplying by 4

`x >> 3; //` shifts bits of `x` three positions right

- ▶ Same as dividing by 8 (if `x` is unsigned)

What does the following do?

```
x = ( ( x >> 2 ) << 2 ) ;
```

- A. Changes x to be positive
- B. Sets the least significant two bits to 0
- C. Sets the most significant two bits to 0
- D. Gives an integer overflow error
- E. Implementation-defined behavior

# Testing if a bit is set (i.e., is 1)

```
#include <stdbool.h>
```

```
// Returns true if the nth bit of x is 1.
```

```
bool is_bit_set(unsigned int x, unsigned int n) {  
    return x & (1u << n); // 1u is an unsigned int with value 1.  
}
```

# Testing if a bit is set (i.e., is 1)

```
#include <stdbool.h>
```

```
// Returns true if the nth bit of x is 1.
```

```
bool is_bit_set(unsigned int x, unsigned int n) {  
    return x & (1u << n); // 1u is an unsigned int with value 1.  
}
```

`1u << n` gives an integer with only the nth bit set

# Testing if a bit is set (i.e., is 1)

```
#include <stdbool.h>
```

```
// Returns true if the nth bit of x is 1.
```

```
bool is_bit_set(unsigned int x, unsigned int n) {  
    return x & (1u << n); // 1u is an unsigned int with value 1.  
}
```

`1u << n` gives an integer with only the nth bit set

If the nth bit is 1, then `x & (1u << n)` is `1u << n` which is nonzero.

If the nth bit is 0, then `x & (1u << n)` is 0

# Testing if a bit is set (i.e., is 1)

```
#include <stdbool.h>
```

```
// Returns true if the nth bit of x is 1.
```

```
bool is_bit_set(unsigned int x, unsigned int n) {  
    return x & (1u << n); // 1u is an unsigned int with value 1.  
}
```

`1u << n` gives an integer with only the nth bit set

If the nth bit is 1, then `x & (1u << n)` is `1u << n` which is nonzero.

If the nth bit is 0, then `x & (1u << n)` is 0

What happens if n is too large?



# Testing if a bit is set (i.e., is 1)

```
#include <stdbool.h>
```

```
// Returns true if the nth bit of x is 1.
```

```
bool is_bit_set(unsigned int x, unsigned int n) {  
    return x & (1u << n); // 1u is an unsigned int with value 1.  
}
```

`1u << n` gives an integer with only the nth bit set

If the nth bit is 1, then `x & (1u << n)` is `1u << n` which is nonzero.

If the nth bit is 0, then `x & (1u << n)` is 0

What happens if n is too large?

- Undefined behavior!

# UB

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# UB

```
$ ./bad_shift 3 0
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# UB

```
$ ./bad_shift 3 0  
Bit 0 of 3 is 1
```

```
#include <err.h>  
#include <stdbool.h>  
#include <stdio.h>  
#include <stdlib.h>  
  
// Returns true if the nth bit of x is 1.  
bool is_bit_set(unsigned int x, unsigned int n) {  
    return x & (1u << n);  
}  
  
int main(int argc, char **argv) {  
    if (argc != 3)  
        errx(1, "Usage: %s integer bit", argv[0]);  
    unsigned int x = atoi(argv[1]);  
    unsigned int n = atoi(argv[2]);  
    if (is_bit_set(x, n))  
        printf("Bit %u of %u is 1\n", n, x);  
    else  
        printf("Bit %u of %u is 0\n", n, x);  
    return 0;  
}
```

# UB

```
$ ./bad_shift 3 0  
Bit 0 of 3 is 1  
$ ./bad_shift 3 1
```

```
#include <err.h>  
#include <stdbool.h>  
#include <stdio.h>  
#include <stdlib.h>  
  
// Returns true if the nth bit of x is 1.  
bool is_bit_set(unsigned int x, unsigned int n) {  
    return x & (1u << n);  
}  
  
int main(int argc, char **argv) {  
    if (argc != 3)  
        errx(1, "Usage: %s integer bit", argv[0]);  
    unsigned int x = atoi(argv[1]);  
    unsigned int n = atoi(argv[2]);  
    if (is_bit_set(x, n))  
        printf("Bit %u of %u is 1\n", n, x);  
    else  
        printf("Bit %u of %u is 0\n", n, x);  
    return 0;  
}
```

# UB

```
$ ./bad_shift 3 0
Bit 0 of 3 is 1
$ ./bad_shift 3 1
Bit 1 of 3 is 1
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# UB

```
$ ./bad_shift 3 0
Bit 0 of 3 is 1
$ ./bad_shift 3 1
Bit 1 of 3 is 1
$ ./bad_shift 3 2
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# UB

```
$ ./bad_shift 3 0
Bit 0 of 3 is 1
$ ./bad_shift 3 1
Bit 1 of 3 is 1
$ ./bad_shift 3 2
Bit 2 of 3 is 0
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```



# UB

```
$ ./bad_shift 3 0
Bit 0 of 3 is 1
$ ./bad_shift 3 1
Bit 1 of 3 is 1
$ ./bad_shift 3 2
Bit 2 of 3 is 0
$ ./bad_shift 3 32
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# UB

```
$ ./bad_shift 3 0
Bit 0 of 3 is 1
$ ./bad_shift 3 1
Bit 1 of 3 is 1
$ ./bad_shift 3 2
Bit 2 of 3 is 0
$ ./bad_shift 3 32
Bit 32 of 3 is 1
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# UB

```
$ ./bad_shift 3 0
Bit 0 of 3 is 1
$ ./bad_shift 3 1
Bit 1 of 3 is 1
$ ./bad_shift 3 2
Bit 2 of 3 is 0
$ ./bad_shift 3 32
Bit 32 of 3 is 1
$ ./bad_shift 3 33
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# UB

```
$ ./bad_shift 3 0
Bit 0 of 3 is 1
$ ./bad_shift 3 1
Bit 1 of 3 is 1
$ ./bad_shift 3 2
Bit 2 of 3 is 0
$ ./bad_shift 3 32
Bit 32 of 3 is 1
$ ./bad_shift 3 33
Bit 33 of 3 is 1
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# UB

```
$ ./bad_shift 3 0
Bit 0 of 3 is 1
$ ./bad_shift 3 1
Bit 1 of 3 is 1
$ ./bad_shift 3 2
Bit 2 of 3 is 0
$ ./bad_shift 3 32
Bit 32 of 3 is 1
$ ./bad_shift 3 33
Bit 33 of 3 is 1
$ ./bad_shift 3 34
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# UB

```
$ ./bad_shift 3 0
Bit 0 of 3 is 1
$ ./bad_shift 3 1
Bit 1 of 3 is 1
$ ./bad_shift 3 2
Bit 2 of 3 is 0
$ ./bad_shift 3 32
Bit 32 of 3 is 1
$ ./bad_shift 3 33
Bit 33 of 3 is 1
$ ./bad_shift 3 34
Bit 34 of 3 is 0
```

```
#include <err.h>
#include <stdbool.h>
#include <stdio.h>
#include <stdlib.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    return x & (1u << n);
}

int main(int argc, char **argv) {
    if (argc != 3)
        errx(1, "Usage: %s integer bit", argv[0]);
    unsigned int x = atoi(argv[1]);
    unsigned int n = atoi(argv[2]);
    if (is_bit_set(x, n))
        printf("Bit %u of %u is 1\n", n, x);
    else
        printf("Bit %u of %u is 0\n", n, x);
    return 0;
}
```

# Testing if a bit is set (i.e., is 1)

```
#include <assert.h>
#include <limits.h>
#include <stdbool.h>
```

```
// Returns true if the nth bit of x is 1.
```

```
bool is_bit_set(unsigned int x, unsigned int n) {
    // assert(cond) will abort at runtime if cond is false.
    assert(n < CHAR_BIT * sizeof x);
    return x & (1u << n); // 1u is an unsigned int with value 1.
}
```

# Testing if a bit is set (i.e., is 1)

```
#include <assert.h>
#include <limits.h>
#include <stdbool.h>

// Returns true if the nth bit of x is 1.
bool is_bit_set(unsigned int x, unsigned int n) {
    // assert(cond) will abort at runtime if cond is false.
    assert(n < CHAR_BIT * sizeof x);
    return x & (1u << n); // 1u is an unsigned int with value 1.
}
```

E.g., if **CHAR\_BIT** is 8 and **sizeof x** is 4, then **n** must be less than 32 or the program aborts



# Setting a bit (to 1)

```
// Returns the value of x with the nth bit set to 1.  
unsigned int set_bit(unsigned int x, unsigned int n) {  
    assert(n < CHAR_BIT * sizeof x);  
    return x | (1u << n);  
}
```

# Clearing a bit (setting it to 0)

```
// Returns the value of x with the nth bit set to 0.
```

```
unsigned int set_bit(unsigned int x, unsigned int n) {  
    assert(n < CHAR_BIT * sizeof x);  
    return x & ~(1u << n);  
}
```

# Clearing a bit (setting it to 0)

```
// Returns the value of x with the nth bit set to 0.
```

```
unsigned int set_bit(unsigned int x, unsigned int n) {  
    assert(n < CHAR_BIT * sizeof x);  
    return x & ~(1u << n);  
}
```

`1u << n` gives an integer with just the nth bit set

# Clearing a bit (setting it to 0)

```
// Returns the value of x with the nth bit set to 0.  
unsigned int set_bit(unsigned int x, unsigned int n) {  
    assert(n < CHAR_BIT * sizeof x);  
    return x & ~(1u << n);  
}
```

`1u << n` gives an integer with just the nth bit set

`~(1u << n)` gives an integer with all bits set *except* the nth bit

Given an unsigned integer `x` with some value, what value should we use for `mask` to clear all of the bits of `x` except for the least significant 5 bits?

```
unsigned int x = /* ... */; // Given some value here,  
unsigned int mask = /* ... */; // what value goes here  
x = x & mask; // to clear the required bits?
```

A. `0x5u`

B. `~0x5u`

C. `0x1Fu`

D. `~0x1Fu`

E. `sizeof x - 5`

Given an unsigned integer `x` with some value, what value should we use for `mask` to clear the 5 least significant bits of `x`?

```
unsigned int x = /* ... */; // Given some value here,  
unsigned int mask = /* ... */; // what value goes here  
x = x & mask; // to clear the required bits?
```

A. `0x5u`

B. `~0x5u`

C. `0x1Fu`

D. `~0x1Fu`

E. `sizeof x - 5`

# Combining flags via |

Specify flags via individual bits

Combine flags with |

E.g., set file system

permissions via the flags

`S_I{R,W,X}{USR,GRP,OTH}`

```
#define S_IRWXU 0000700 /* RWX mask for owner */
#define S_IRUSR 0000400 /* R for owner */
#define S_IWUSR 0000200 /* W for owner */
#define S_IXUSR 0000100 /* X for owner */
```

```
#define S_IRWXG 0000070 /* RWX mask for group */
#define S_IRGRP 0000040 /* R for group */
#define S_IWGRP 0000020 /* W for group */
#define S_IXGRP 0000010 /* X for group */
```

```
#define S_IRWXO 0000007 /* RWX mask for other */
#define S_IROTH 0000004 /* R for other */
#define S_IWOTH 0000002 /* W for other */
#define S_IXOTH 0000001 /* X for other */
```

```
int chmod(char const *path, mode_t mode);
```

# Negative numbers



# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits  
magnitude:     0000\_0101

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

magnitude: 0000\_0101

invert bits: 1111\_1010

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

magnitude: 0000\_0101

invert bits: 1111\_1010

Add 1: 1111\_1011

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

Computing  $-x$  from  $x$  (regardless of sign)

- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

magnitude:     0000\_0101

invert bits:    1111\_1010

Add 1:         1111\_1011

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

Computing  $-x$  from  $x$  (regardless of sign)

- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

magnitude: 0000\_0101

invert bits: 1111\_1010

Add 1: 1111\_1011

$-(-5)$  in 8 bits

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

Computing  $-x$  from  $x$  (regardless of sign)

- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

magnitude: 0000\_0101

invert bits: 1111\_1010

Add 1: 1111\_1011

$-(-5)$  in 8 bits

-5: 1111\_1011



# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

Computing  $-x$  from  $x$  (regardless of sign)

- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

magnitude: 0000\_0101

invert bits: 1111\_1010

Add 1: 1111\_1011

$-(-5)$  in 8 bits

-5: 1111\_1011

invert bits: 0000\_0100

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

Computing  $-x$  from  $x$  (regardless of sign)

- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

```
magnitude:    0000_0101
invert bits:   1111_1010
Add 1:        1111_1011
```

$-(-5)$  in 8 bits

```
-5:           1111_1011
invert bits:  0000_0100
Add 1:       0000_0101
```

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

Computing  $-x$  from  $x$  (regardless of sign)

- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits  
magnitude: 0000\_0101  
invert bits: 1111\_1010  
Add 1: 1111\_1011

$-(-5)$  in 8 bits  
-5: 1111\_1011  
invert bits: 0000\_0100  
Add 1: 0000\_0101  
  
0: 0000\_0000

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

Computing  $-x$  from  $x$  (regardless of sign)

- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

```
magnitude: 0000_0101
invert bits: 1111_1010
Add 1:      1111_1011
```

$-(-5)$  in 8 bits

```
-5: 1111_1011
invert bits: 0000_0100
Add 1: 0000_0101
```

```
0: 0000_0000
invert bits: 1111_1111
```

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

Computing  $-x$  from  $x$  (regardless of sign)

- ▶ Invert all of the bits
- ▶ Add 1

representation of -5 in 8 bits

```
magnitude: 0000_0101
invert bits: 1111_1010
Add 1:      1111_1011
```

$-(-5)$  in 8 bits

```
-5: 1111_1011
invert bits: 0000_0100
Add 1: 0000_0101
```

```
0: 0000_0000
invert bits: 1111_1111
Add 1: 1_0000_0000
```

# Negative numbers

Usually stored using two's complement

- ▶ Take the magnitude of the number
- ▶ Invert all of the bits
- ▶ Add 1

Computing  $-x$  from  $x$  (regardless of sign)

- ▶ Invert all of the bits
- ▶ Add 1

Most significant bit indicates the sign

- ▶ 1 indicates a negative number

representation of -5 in 8 bits

```
magnitude: 0000_0101
invert bits: 1111_1010
Add 1:      1111_1011
```

$-(-5)$  in 8 bits

```
-5: 1111_1011
invert bits: 0000_0100
Add 1: 0000_0101
```

```
0: 0000_0000
invert bits: 1111_1111
Add 1: 1_0000_0000
```

# Signed numbers in two's complement

|          |          |          |          |   |             |
|----------|----------|----------|----------|---|-------------|
| 10000000 | 00000000 | 00000000 | 00000000 | = | $-2^{31}$   |
| 10000000 | 00000000 | 00000000 | 00000001 | = | $-2^{31}+1$ |
| ...      |          |          |          |   |             |
| 11111111 | 11111111 | 11111111 | 11111110 | = | $-2$        |
| 11111111 | 11111111 | 11111111 | 11111111 | = | $-1$        |
| 00000000 | 00000000 | 00000000 | 00000000 | = | $0$         |
| 00000000 | 00000000 | 00000000 | 00000001 | = | $1$         |
| 00000000 | 00000000 | 00000000 | 00000010 | = | $2$         |
| 00000000 | 00000000 | 00000000 | 00000011 | = | $3$         |
| ...      |          |          |          |   |             |
| 01111111 | 11111111 | 11111111 | 11111110 | = | $2^{31}-2$  |
| 01111111 | 11111111 | 11111111 | 11111111 | = | $2^{31}-1$  |

# Not the only choice



# Not the only choice

## Sign and magnitude

- ▶ Most significant bit represents the sign, remaining bits are the magnitude
- ▶ Range  $-(2^{n-1} - 1)$  to  $2^{n-1} - 1$
- ▶ Two different bit patterns for zero: 0 and 0x80000000 (assuming 32-bits)

# Not the only choice

## Sign and magnitude

- ▶ Most significant bit represents the sign, remaining bits are the magnitude
- ▶ Range  $-(2^{n-1} - 1)$  to  $2^{n-1} - 1$
- ▶ Two different bit patterns for zero: 0 and 0x80000000 (assuming 32-bits)

## Ones' complement

- ▶ Negative numbers are the bitwise inverse of positive numbers ( $-x = \sim x$ )
- ▶ Range  $-(2^{n-1} - 1)$  to  $2^{n-1} - 1$
- ▶ Two different bit patterns for zero: 0 and 0xFFFFFFFF (assuming 32-bits)

# Not the only choice

## Sign and magnitude

- ▶ Most significant bit represents the sign, remaining bits are the magnitude
- ▶ Range  $-(2^{n-1} - 1)$  to  $2^{n-1} - 1$
- ▶ Two different bit patterns for zero: 0 and 0x80000000 (assuming 32-bits)

## Ones' complement

- ▶ Negative numbers are the bitwise inverse of positive numbers ( $-x = \sim x$ )
- ▶ Range  $-(2^{n-1} - 1)$  to  $2^{n-1} - 1$
- ▶ Two different bit patterns for zero: 0 and 0xFFFFFFFF (assuming 32-bits)

## Two's complement

- ▶ Negative numbers are ones' complement plus one ( $-x = \sim x + 1$ )
- ▶ Range  $-2^{n-1}$  to  $2^{n-1} - 1$
- ▶ Only one zero

# In-class exercise

<https://checkoway.net/teaching/cs241/2019-fall/exercises/Lecture-13.html>

Grab a laptop and a partner and try to get as much of that done as you can!