

CS 241: Systems Programming

Lecture 9. More C

Spring 2020
Prof. Stephen Checkoway

Operators

The same as Java

- ▶ Arithmetic: +, -, *, /, %
- ▶ Logical: &&, ||, !
- ▶ Bitwise: &, |, ^, ~, <<, >>
- ▶ Pre/post increment, decrement: ++, --
- ▶ Relational: ==, !=, <, <=, >, >=
- ▶ Assignment: =, +=, -=, *=, /=, %=, &=, |=, ^=, <<=, >>=

There are some others we'll talk about later

- ▶ `sizeof`
- ▶ `.`
- ▶ `->`

C has pre- and post-increment (++) and -decrement (--) operators. What does this code print? (%d means print an integer)

```
int main(void) {  
    int x = 3;  
    int y = 5;  
    printf("%d %d\n", x--, ++y);  
    return 0;  
}
```

A. 2 5

B. 2 6

C. 3 5

D. 3 6

E. Undefined

C has pre- and post-increment (++) and -decrement (--) operators. What does this code print? (%d means print an integer)

```
int main(void) {
    int x = 3;
    printf("%d\n", x-- + --x);
    return 0;
}
```

A. 3

B. 4

C. 5

D. 6

E. Undefined

Huge difference from Java

C is **full** of undefined behavior, implementation-defined behavior, and unspecified behavior

Undefined behavior gives the compiler license to do whatever it wants, including nothing

Implementation-defined behavior means the compiler gets to choose (and document) its behavior

Unspecified behavior means the compiler gets to pick from among several choices

What does the code print?

- A. foo
bar
1 2
- B. bar
foo
1 2
- C. 1 2
foo
bar
- D. Undefined behavior, could print anything
- E. Unspecified behavior, either A or B.

```
#include <stdio.h>
```

```
int foo(void) {  
    printf("foo\n");  
    return 1;  
}
```

```
int bar(void) {  
    printf("bar\n");  
    return 2;  
}
```

```
int main(void) {  
    printf("%d %d\n", foo(), bar());  
    return 0;  
}
```

Control flow

if statements; **for**, **while**, **do-while** loops almost identical to Java
zero is **false**, nonzero is **true**

Examples

```
int signum(int x) {  
    if (x < 0)  
        return -1;  
    if (x > 0)  
        return 1;  
    return 0;  
}
```

```
int sum_of_squares(int n) {  
    int result = 0;  
    for (int i = 1; i < n; ++i)  
        result += i * i;  
    return result;  
}
```

Examples

```
bool get_reponse(void) {
    int response;
    do {
        printf("Enter y or n\n");
        response = getchar();
    } while (response != EOF
              && response != 'y'
              && response != 'n');
    return response == 'y';
}
```

Compiling code

```
$ <compiler> <options> <.c files> <libraries>
```

```
$ clang -Wall -o program -std=c11 *.c -lm
```

If you omit `-o output`, the default is `a.out`

If you omit `-std=c11`, `clang` and `gcc` have different defaults!

Compiler options (gcc/clang)

Compiler options (gcc/clang)

-E preprocessor only

Compiler options (gcc/clang)

- E preprocessor only
- S compile only (no assembly or linking)

Compiler options (gcc/clang)

- E preprocessor only
- S compile only (no assembly or linking)
- c compile/assemble (produce .o file)

Compiler options (gcc/clang)

- E preprocessor only
- S compile only (no assembly or linking)
- c compile/assemble (produce .o file)
- o **foo** specify output file as **foo**

Compiler options (gcc/clang)

- E preprocessor only
- S compile only (no assembly or linking)
- c compile/assemble (produce .o file)
- o **foo** specify output file as **foo**
- l**xxx** use library named lib**xxx**.so or lib**xxx**.a

Compiler options (gcc/clang)

-E	preprocessor only
-S	compile only (no assembly or linking)
-c	compile/assemble (produce .o file)
-o <code>foo</code>	specify output file as <code>foo</code>
-l <code>xxx</code>	use library named <code>libxxx.so</code> or <code>libxxx.a</code>
-g	emit debugging symbols (enables debugging)

Compiler options (gcc/clang)

-E	preprocessor only
-S	compile only (no assembly or linking)
-c	compile/assemble (produce .o file)
-o <code>foo</code>	specify output file as <code>foo</code>
-l <code>xxx</code>	use library named <code>libxxx.so</code> or <code>libxxx.a</code>
-g	emit debugging symbols (enables debugging)
-std=c11	use C11 standard

Compiler options (gcc/clang)

-E	preprocessor only
-S	compile only (no assembly or linking)
-c	compile/assemble (produce .o file)
-o <code>foo</code>	specify output file as <code>foo</code>
-l <code>xxx</code>	use library named <code>libxxx.so</code> or <code>libxxx.a</code>
-g	emit debugging symbols (enables debugging)
-std=c11	use C11 standard
-pedantic	be pedantic
<code>-Wall</code>	turn on "all" warnings
<code>-Wextra</code>	turn on extra warnings
<code>-Werror</code>	make warnings into errors

Formatting your code

It's more important to be consistent than anything else when it comes to format

Use tools!

```
$ clang-format foo.c          # Writes formatted code to stdout
```

```
$ clang-format -i foo.c      # Writes formatted code back to foo.c
```

In-class exercise

<https://checkoway.net/teaching/cs241/2020-spring/exercises/Lecture-09.html>

Grab a laptop and a partner and try to get as much of that done as you can!